

**RECEIVED
CENTRAL FAX CENTER****MAR 26 2008**

Application No. 10/542,654

Attorney Docket No. 57.0513 US PCT

Amendment dated March 26, 2008

Reply to Office Action dated December 26, 2007

AMENDMENT TO THE CLAIMS

Please **AMEND** claims 1-3, 5, 11, 20-22, 27, 30, 36-38, 40-41, 43-44, 46, 50
and 53-54.

Please **ADD** claims 61-66.

Please **WITHDRAW** claims 55-56.

Please **CANCEL** claims 12, 14, 28 and 34.

No new matter has been added. This listing of claims will replace all prior
versions, and listings, of claims in the application.

Listing of Claims

1. (Currently amended) A system for maintaining zonal isolation in a wellbore, characterized in that said system comprises, within a pathway at a specific location along said wellbore, a sealing element to block said pathway, said sealing element being able to deform both during and after placement and wherein the sealing element is maintained under compression after completion of the placement, thereby urging the deformable sealing element into contact with less deformable material bounding the pathway so as to maintain a seal against fluid migration along the pathway.
2. (Currently amended) The system of claim 1, wherein the sealing element is connected to a fluid communication element ~~designed to pressurize~~ adapted to supply pressurizing fluid after placement and thereby maintain pressure within at least part of the sealing element.
3. (Currently amended) The system of claim 1, wherein the sealing element is confined in a volume surrounded by materials of high Young's modulus, greater than 1000MPa, and the sealing element comprises a sealing material, which has a Young's modulus below 1000 MPa.

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

4. (Original) The system of claim 1, wherein the sealing element comprises a sealing material in a solid state.
5. (Currently amended) The system of claim 1, wherein the sealing element comprises a sealing material which approximates the behaviour of an elastic solid.
6. (Original) The system of claim 1, wherein the sealing element comprises a sealing material in a liquid state.
7. (Previously presented) The system of claim 1, wherein the sealing element comprises a sealing material, said sealing material being a yield stress fluid.
8. (Previously presented) The system of claim 7, wherein the yield stress value of the sealing material is greater than 10 Pa.
9. (Original) The system of claim 1, wherein the sealing material is visco-plastic.
10. (Original) The system of claim 1, wherein the sealing material is visco-elastic.
11. (Currently amended) The system of claim 1, wherein the sealing element is composite and comprises a first material which forms a continuous phase and a second material which forms a discontinuous phase.
12. (Cancelled).
13. (Original) The system of claim 1, wherein the sealing element comprises an inflatable membrane.

Appl. No. 10/542,654
Amtd. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT.

14. (Cancelled).
15. (Original) The system of claim 1, wherein the sealing element is able to deform elastically for an extended period of time after placement.
16. (Previously presented) The system of claim 1, wherein the sealing element is able to deform for more than 7 days after placement.
17. (Original) The system of claim 1, wherein the sealing element is designed to deform for the planned life time of the well.
18. (Previously presented) The system of claim 1, wherein formation surrounding the wellbore comprises at least a first layer and a second layer, said first layer being essentially impermeable and said second layer being permeable and wherein the sealing element is at least partially placed adjacent to the first layer.
19. (Original) The system of claim 1, wherein the sealing element is a sealing ring, said sealing ring being placed in an annulus between well tubing and formation surrounding the wellbore.
20. (Currently amended) The system of claim 3, wherein the sealing element is a sealing ring, said sealing ring being placed in a volume formed by well tubing, formation surrounding the wellbore and cement injected into the wellbore.
21. (Currently amended) The system of claim 20, wherein the cement sheath injected into the wellbore comprises a first sheath portion and a second sheath portion and wherein the sealing ring is contained between and contacts said first sheath portion and said second portion.

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

22. (Currently amended) The system of claim 20, wherein the cement ~~sheath~~ injected into the wellbore comprises material that expands after placement.
23. (Previously presented) The system of claim 19, wherein the well tubing is expandable and the sealing element is fixed on the outside of said expandable well tubing.
24. (Original) The system of claim 1, wherein the average height of the sealing element, measured along the wellbore axis, is less than approximately 150 m.
25. (Original) The system of claim 24, wherein the average height of the sealing element, measured along the wellbore axis, is less than approximately 60 m.
26. (Original) The system of claim 25, wherein the average height of the sealing element, measured along the wellbore axis, is comprised between approximately 1 m and approximately 30 m.
27. (Currently amended) The system of claim 1, wherein the sealing element comprises a sealing material, which is sufficiently fluid prior to placement to be pumped or injected at a specific downhole location, and sets under pressure to a deformable solid or a yield stress fluid.
28. (Cancelled).
29. (Previously presented) The system of claim 27, wherein said sealing material expands during solidification or gelation.
30. (Currently amended) The system of claim 3, wherein the sealing material is maintained under compression by one or more cement sheath portions.

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

31. (Original) The system of claim 3, wherein the sealing element is compressed by expanded parts of a well tube.
32. (Original) The system of claim 3, wherein the sealing element consists of a chemical compound that homogenously fills the volume.
33. (Original) The system of claim 2, wherein compression results from the hydrostatic pressure of the liquid/yield fluid that forms the sealing material.
34. (Cancelled)
35. (Original) The system of claim 1, wherein the sealing element comprises an elastic tube adapted to make a sealing contact with the formation.
36. (Currently amended) A method of maintaining zonal isolation in a wellbore, characterized in that it comprises the following steps:
placing a sealing element within a pathway at a specific location along said wellbore;
allowing said sealing element to be able to deform both during and after placement; and
maintaining the sealing element under compression after completion of the placement, thereby urging the deformable sealing element into contact with less deformable material bounding the pathway so as to maintain a seal against fluid migration along the pathway.
37. (Currently amended) ~~The method of claim 36 wherein maintaining the sealing element under compression after completion of the placement includes the step of~~ A method of maintaining zonal isolation in a wellbore, characterized in that it comprises the following steps:

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

placing a sealing element at a specific location along said wellbore;
allowing said sealing element to be able to deform both during and
after placement; and
maintaining the sealing element under compression after completion of
the placement by exerting pressure on the sealing element through a
permanent fluid communication element.

38. (Currently amended) The method of claim 36 wherein maintaining the sealing element under compression after completion of the placement includes the step of confining the sealing element in a volume surrounded by materials of high Young's modulus greater than 1000MPa, and the sealing element comprises a sealing material, which has a Young's modulus below 1000 MPa.

39. (Previously presented) The method of claim 36, wherein the sealing element comprises a sealing material, which is a liquid or a gel, said sealing material being activated to transform to a solid or yield stress fluid.

40. (Currently amended) ~~The method of claim 39;~~ A method of maintaining zonal isolation in a wellbore, characterized in that it comprises the following steps:

placing a sealing element at a specific location along said wellbore,
said sealing element comprising a sealing material;

allowing said sealing element to be able to deform both during and
after placement;

activating said sealing material to transform to a solid or yield stress
fluid, and

thereafter maintaining the sealing element under compression after
completion of the placement,

wherein the activation is triggered by expansion of parts of a well tube crushing encapsulated components of the sealing material, by an external trigger, or by injection of an activator.

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

41. (Currently amended) The method of claim 36, wherein there is a well tube within said well bore and the sealing element is placed on the outer surface of said well tube.
42. (Previously presented) The method of claim 36, wherein the sealing element comprises an inflatable element, said inflatable element being inflated by a sealing material, in a liquid or gel state.
43. (Currently amended) The method of claim 36, wherein there is a well tube within said well bore and at least part of the sealing material is placed after placement of the well tube.
44. (Currently amended) The method of claim ~~36~~ 43, wherein the sealing material is pumped from the surface through one or more ports in the well tube.
45. (Original) The method of claim 44, wherein the well tube comprises a valve, which is able to open or close said one or more ports.
46. (Currently amended) The method of claim 36, wherein there is a well tube within said well bore and the sealing material is pumped from surface into the annulus between the well tube and the formation.
47. (Original) The method of claim 37, wherein the fluid communication element is a control line tube between surface and the sealing element.
48. (Original) The method of claim 36, wherein the sealing element is pumped as part of a fluid train from the surface through a well tubing into the annulus between the well tubing and the formation.

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

49. (Original) The method of claim 48, wherein the sealing element is placed using a delivery tube introduced into the well tube.
50. (Currently amended) The method of claim 36, wherein there is a well tube within said well bore and the sealing element comprises an inflatable element placed in the annulus between the well tube and the wellbore, independently of the well tube.
51. (Original) The method of claim 36, wherein the sealing element has an essentially full cylindrical or disk shape to seal the full cross-section of the well.
52. (Original) The method of claim 36, wherein an under-reaming is carried out and the sealing material is placed in the under-reamed section of the well.
53. (Currently amended) The ~~method or~~ system of claim 1, comprising a plurality of said sealing elements at respective specific locations along said wellbore.
54. (Currently amended) Use of the ~~method or the~~ system according to claim 1 ~~or~~ 36 for plug and abandonment.
55. (Withdrawn) Wellbore fluid comprising crosslinkable polypropylene glycol adapted for injection in the well to cause the formation of a permanent barrier to isolate sections of the wellbore.
56. (Withdrawn) The wellbore fluid of claim 55 wherein the polypropylene glycol comprises epoxy groups as terminal groups.
57. (Previously presented) The system of claim 7, wherein the stress value of the sealing material is greater than 600Pa.

Appl. No. 10/542,654
Amdt. dated March 26, 2008
Reply to Office Action of December 26, 2007

PATENT
Docket No.: 57.0513 US PCT

58. (Previously presented) The system of claim 1, wherein the sealing element is able to deform for more than one month after placement.
59. (Previously presented) The method of claim 39 wherein said sealing material is a liquid.
60. (Previously presented) The method of claim 39 wherein said sealing material is a gel.
61. (New) The system of claim 1, wherein the sealing element is able to deform for at least 5 years after placement.
62. (New) The method of claim 36, comprising placing a plurality of said sealing elements at respective specific locations along said wellbore.
63. (New) Use of the method according to claim 36 for plug and abandonment.
64. (New) The system of claim 1, wherein said pathway is at least partially bounded by rock or cement.
65. (New) The method of claim 36, wherein said pathway is at least partially bounded by rock or cement.
66. (New) The method of claim 36, comprising maintaining the sealing element under compression and able to deform for more than one month after placement.